



RETROREFLECTIVE TAB

RETROREFLECTOR TABS SHALL BE 12 TO 14 GAUGE STEEL AND SHALL BE TRAPEZOIDAL (BUTTERFLY) REFLECTORS MANUFACTURED BY TAPCO OR APPROVED EQUAL.

RETROREFLECTOR TABS SHALL BE INSTALLED AT 25 FT. INTERVALS ON ALL NEW AND EXISTING GUARDRAIL.

THE TABS SHALL BE INSTALLED ON SPLICE BOLTS, NOT ON POST BOLTS AND SHALL BE MOUNTED SO THE BOLT SLOT FACES AWAY FROM TRAFFIC, AND THE RETROREFLECTOR SURFACE FACES THE APPROACHING TRAFFIC FOR ONE-WAY ROADS.

FOR TWO-WAY ROADS, BOTH SIDES OF THE TABS SHALL BE RETROREFLECTIVE, SO THAT DELINEATION IS PROVIDED FOR BOTH DIRECTIONS OF TRAVEL.

THE RETROREFLECTIVE SHEETING COLOR SHALL MATCH THE COLOR OF THE ADJACENT TRAVEL WAY EDGE LINE.

THE RETROREFLECTIVE SHEETING SHALL CONFORM TO ASTM D4956 TYPE III.